

Centon



Serene SR711 *Series*

INSTANT WATER HEATER



Export
Excellence
Award
2019

Image for illustration purposes only.
Please consult a certified plumber and obey all building regulations.



Full Specifications



Stepless Electronic Control

Allows users to make fine power adjustment to produce desired shower temperature.



Built-in Residual Current Device (RCD)

Automatically Power supply cuts off in the event of current leakage.



Built-in Flow Sensor

Cuts off power in the event water flow is less than the rated flow.



Double Function Thermostat

Protects from the risk of scalding in case of overly high temperature.



Splash Proof Casing

Protection against water jet spray from all possible directions.



Multi-spray Hand Shower

Shower Hand Set selection allows users to select preferred shower spray pattern for optimum shower sensation.



Built-in DC Silent Pump (Optional)

Advanced 3-phase brushless DC motor that generate high flow rate & consumes 50% lower electrical power than normal AC motor.



Built-in Voltage Surge Protector

Protects internal electrical circuit from electrical surges and voltage spikes, including those caused by lightning.



UK Technology Heating Element

Advanced heating technology providing users with instant hot shower water flow, with a guaranteed 5-year warranty.



Unlimited Capacity Hot Water Supply

Tankless instantaneous water heater technology provides on-demand constant supply of hot water instantly.



Triple Function Right Angle Stop Valve

Smooth 90° water flow control valve with regulator and built-in mesh filter to prevent foreign particles from flowing into the heating element, causing unwanted damages / blockages.



DOUBLE FUNCTION THERMOSTAT
Maintains safe water output temperature at all times.



SPLASH PROOF CASING
Protects electrical components against water jet spray.



RCD
Cuts off power supply in the event of current leakage.
selected models only



FLOW SENSOR
Prevents overheating due to insufficient water supply.



NON CONDUCTIVE HOSE
Protects against fatal electrical currents.
selected models only

PENTAFECTA
5-POINT SAFETY SYSTEM BY **Centon**

Distributed by

CENTON HOME APPLIANCES SDN. BHD. [1289180-P]

21, Jalan Seruling 58, Taman Klang Jaya,
41200 Klang, Selangor, Malaysia



www.centon.my



support@centonia.my

Technical Data

Heater Electrical Rating

4.2kW, 220V - 240Vac, 50/60Hz

Min. Water Flow Rate

2 litre / min

Max. Water Pressure

0.38Mpa (3.8bar / 55psi)

Water Temp. Control

Electronic Control

Water Connection

15mm dia. (1/2" BSP)

Heater Dimensions

239mm x 392mm x 99mm (H)

Heater Weight

No Pump : 1.7kg, DC Pump : 2.0kg,

Rainshower : + 2.0kg

DC Pump Electrical Rating (Motor)

Hand Set Models : 36W, 24Vdc

Rain Shower Set Models : 55W, 24Vdc

Shower Set

Choice of Rain Shower or Hand Shower



e-Warranty System

Register & check for remaining warranty period ONLINE

10 YEARS

Anti-Leak Tank

5 YEARS

Heating Element

5 YEARS

DC Silent Pump

1 YEAR

Other Electrical & Electronic Parts



FIND IT
ONLINE
AT

Centon
-my



/centonmy